



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	16-0160	UPDATED TO NEW STANDARDS. -1 CH'D DIM WAS $\varnothing.551+/.005/-0.000$ THRU ALL IS $\varnothing.564/.562$ THRU ALL WAS $\varnothing.8660/.8655$ IS $\varnothing.876/.874$, WAS $\varnothing.728 \pm .80$ M20X1.5 - 6H $\pm .80$; ADDED DIM .750. -3 CH'D MAT'L WAS 1018 IS 1018/1020 CR. -5 CH'D MATERIAL, WAS 1018 IS 1018/1020 CR; CH'D DIM WAS M12x1.5 IS M12x1.5 - 6g; ADDED DIM SR.313. -7 CH'D MATERIAL WAS 4140 Q&T IS 303 S.S.; REMOVED FINISH; REMOVED DIM M5X0.8 - 6H $\pm .39$, $\varnothing.317$, .230; CH'D DIM WAS 1.968 IS 2.22, WAS $\varnothing.8652/.8648$ IS 2X $\varnothing.872/.871$; ADDED DIM .145/.140, .25, 2X R.005, 2X R.01, $\varnothing.698/.696$. -9 CH'D MATERIAL WAS 4140 Q&T IS 303 S.S.; REMOVED FINISH; REMOVED DIM R.04; CH'D DIM WAS $\varnothing.548+0.000/-0.005$ IS 2X $\varnothing.560/.559$, WAS .275 IS .45; ADDED DIM $\varnothing.386/.384$, .145/.140, .155, 2X R.01, 2X R.005, .250, R.313.	10/11/2016	SM	JAG



NOTES:



1. REF. EUROCOPTER T/N: 1X56122294.
2. ALSO IN KIT RBEA62316.

DART AEROSPACE																											
TITLE PUSH-OUT DEVICE																											
DWG NO. RBE1X56-122-294	REV 1																										
<table border="1"> <tr> <td>MAT'L</td> <td>UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td>HEAT TREAT</td> <td>DIMENSIONS ARE IN INCHES</td> </tr> <tr> <td>FINISH</td> <td>.XXX \pm .005 FRACTIONS \pm 1/8</td> </tr> <tr> <td></td> <td>.XX \pm .01 ANGLES \pm 5°</td> </tr> <tr> <td></td> <td>.X \pm .1 SURFACES = 125✓</td> </tr> <tr> <td>SPEC</td> <td>1. BREAK ALL SHARP EDGES .015 x 45° OR .015R</td> </tr> <tr> <td>DRAWN BY: GILBERT</td> <td>2. DIMENSIONAL LIMITS APPLY AFTER PLATING</td> </tr> <tr> <td>CHECKED: CLOUGH</td> <td>3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009</td> </tr> <tr> <td>OPPS APPR: ANDERSON</td> <td>USED ON MODEL</td> </tr> <tr> <td>QA APPR: LINDSAY</td> <td>EC135</td> </tr> <tr> <td>APPROVED: GILBERT</td> <td></td> </tr> <tr> <td>SCALE 1:3</td> <td>DATE 4/11/2012</td> </tr> <tr> <td colspan="2">SHEET 1 OF 6</td> </tr> </table>		MAT'L	UNLESS OTHERWISE SPECIFIED	HEAT TREAT	DIMENSIONS ARE IN INCHES	FINISH	.XXX \pm .005 FRACTIONS \pm 1/8		.XX \pm .01 ANGLES \pm 5°		.X \pm .1 SURFACES = 125✓	SPEC	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	DRAWN BY: GILBERT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING	CHECKED: CLOUGH	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	OPPS APPR: ANDERSON	USED ON MODEL	QA APPR: LINDSAY	EC135	APPROVED: GILBERT		SCALE 1:3	DATE 4/11/2012	SHEET 1 OF 6	
MAT'L	UNLESS OTHERWISE SPECIFIED																										
HEAT TREAT	DIMENSIONS ARE IN INCHES																										
FINISH	.XXX \pm .005 FRACTIONS \pm 1/8																										
	.XX \pm .01 ANGLES \pm 5°																										
	.X \pm .1 SURFACES = 125✓																										
SPEC	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R																										
DRAWN BY: GILBERT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING																										
CHECKED: CLOUGH	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009																										
OPPS APPR: ANDERSON	USED ON MODEL																										
QA APPR: LINDSAY	EC135																										
APPROVED: GILBERT																											
SCALE 1:3	DATE 4/11/2012																										
SHEET 1 OF 6																											

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	OUTSIDE ROD	4140/4142		2
			-3	1	PLUG	1018/1020 CR		3
			-5	1	THREADED ROD	1018/1020 CR		4
			-7	1	LARGE PISTON	303 S.S.		5
			-9	1	SMALL PISTON	303 S.S.		6
		B/O	-19	1	LARGE O-RING	VITON	DASH # 115 (MCMASTER-CARR # 8297T174)	1
		B/O	-21	1	SMALL O-RING	VITON	DASH # 110 (MCMASTER-CARR # 8297T169)	1

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	16-0160	-1 CH'D MATERIAL WAS 4140 IS 4140/4142; CH'D DIM WAS Ø.551+.005/- .000 THRU ALL IS Ø.564/.562 THRU ALL, WAS Ø.8660/.8655 IS Ø.876/.874, WAS Ø.728 ∇ .80 M20X1.5 - 6H ∇ .70 IS M20X1.5 - 6H ∇ .80; ADDED DIM .750.	10/11/2016	SM	JAG



SECTION A-A




(1)

OUTSIDE ROD

DART AEROSPACE													
TITLE PUSH-OUT DEVICE													
DWG NO. RBE1X56-122-294-1	REV 1												
<table border="0"> <tr> <td>MAT'L 4140/4142</td> <td>UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td>HEAT HRC 28-34</td> <td>DIMENSIONS ARE IN INCHES</td> </tr> <tr> <td>FINISH BLACK OXIDE</td> <td>.XXX $\pm .005$ FRACTIONS $\pm 1/8$</td> </tr> <tr> <td>SPEC</td> <td>.XX $\pm .01$ ANGLES $\pm .5^\circ$</td> </tr> <tr> <td></td> <td>.X $\pm .1$ SURFACES = 125</td> </tr> </table>		MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED	HEAT HRC 28-34	DIMENSIONS ARE IN INCHES	FINISH BLACK OXIDE	.XXX $\pm .005$ FRACTIONS $\pm 1/8$	SPEC	.XX $\pm .01$ ANGLES $\pm .5^\circ$.X $\pm .1$ SURFACES = 125		
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED												
HEAT HRC 28-34	DIMENSIONS ARE IN INCHES												
FINISH BLACK OXIDE	.XXX $\pm .005$ FRACTIONS $\pm 1/8$												
SPEC	.XX $\pm .01$ ANGLES $\pm .5^\circ$												
	.X $\pm .1$ SURFACES = 125												
<table border="0"> <tr> <td>DRAWN BY: GILBERT</td> <td>1. BREAK ALL SHARP EDGES</td> </tr> <tr> <td>CHECKED: CLOUGH</td> <td>.015 x 45° OR .015R</td> </tr> <tr> <td>OPPS APPR: ANDERSON</td> <td>2. DIMENSIONAL LIMITS APPLY</td> </tr> <tr> <td>QA APPR: LINDSAY</td> <td>AFTER PLATING</td> </tr> <tr> <td>APPROVED: GILBERT</td> <td>3. INTERPRET DIM AND TOL PER</td> </tr> <tr> <td></td> <td>ASME Y14.5M-2009</td> </tr> </table>		DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES	CHECKED: CLOUGH	.015 x 45° OR .015R	OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY	QA APPR: LINDSAY	AFTER PLATING	APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER		ASME Y14.5M-2009
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES												
CHECKED: CLOUGH	.015 x 45° OR .015R												
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY												
QA APPR: LINDSAY	AFTER PLATING												
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER												
	ASME Y14.5M-2009												
USED ON MODEL EC135													
SCALE 1:2	DATE 4/11/2012												
SHEET 2 OF 6													

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	16-0160	-3 CH'D MATERIAL WAS 1018 IS 1018/1020 CR.	10/11/2016	SM	JAG






(-3)

PLUG

DART AEROSPACE	
TITLE PUSH-OUT DEVICE	
DWG NO. RBE1X56-122-294-3	REV 1
MAT'L 1018/1020 CR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC	.XX ± .01 ANGLES ± 5°
	.X ± .1 SURFACES = 125° ✓
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
SCALE 1:1	DATE 6/14/2012
	USED ON MODEL EC135
	SHEET 3 OF 6

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	16-0160	-5 CH'D MATERIAL, WAS 1018 IS 1018/1020 CR; CH'D DIM WAS M12x1.5 IS M12x1.5 - 6g; ADDED DIM SR.313.	10/11/2016	SM	JAG




(-5)

THREADED ROD

DART AEROSPACE	
TITLE PUSH-OUT DEVICE	
DWG NO. RBE1X56-122-294-5	REV 1
MAT'L 1018/1020 CR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC	.XX ± .01 ANGLES ± 5°
	.X ± .1 SURFACES = 125° ✓
DRAWN BY: GILBERT	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
SCALE 1:1	DATE 6/14/2012
	SHEET 4 OF 6

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	16-0160	-7 CH'D MATERIAL WAS 4140 Q&T IS 303 S.S.; REMOVED FINISH; REMOVED DIM M5X0.8 - 6H Ψ .39, Φ .317, .230; CH'D DIM WAS 1.968 IS 2.22, WAS Φ .8652/.8648 IS 2X Φ .872/.871; ADDED DIM .145/.140, .25, 2X R.005, 2X R.01, Φ .698/.696.	10/11/2016	SM	JAG







(-7)

PISTON

DART AEROSPACE	
TITLE PUSH-OUT DEVICE	
DWG NO. RBE1X56-122-294-7	REV 1
MAT'L 303 S.S.	UNLESS OTHERWISE SPECIFIED
HEAT TREAT FINISH	DIMENSIONS ARE IN INCHES
SPEC	.XXX \pm .005 FRACTIONS \pm 1/8
DRAWN BY: GILBERT	.XX \pm .01 ANGLES \pm 5°
CHECKED: CLOUGH	.X \pm .1 SURFACES = 125°
OPPS APPR: ANDERSON	1. BREAK ALL SHARP EDGES
QA APPR: LINDSAY	.015 x 45° OR .015R
APPROVED: GILBERT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
SCALE 2:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 6/14/2012	USED ON MODEL
SHEET 5 OF 6	EC135

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1	16-0160	-9 CH'D MATERIAL WAS 4140 Q&T IS 303 S.S.; REMOVED FINISH; REMOVED DIM R.04; CH'D DIM WAS $\varnothing .548 \pm .000 / -.005$ IS $2X \varnothing .560 / .559$, WAS .275 IS .45; ADDED DIM $\varnothing .386 / .384$, .145 / .140, .155, 2X R.01, 2X R.005, .250, R.313.	10/11/2016	SM	JAG



SECTION B-B

⑨

INSERT

DART AEROSPACE	
TITLE PUSH-OUT DEVICE	
DWG NO. RBE1X56-122-294-9	REV 1
MAT'L 303 S.S. HEAT TREAT FINISH SPEC	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± .5° .X ± .1 SURFACES = 125° ✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: GILBERT	USED ON MODEL
CHECKED: CLOUGH	EC135
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 3:1	DATE 6/14/2016
SHEET 6 OF 6	